


SMD Multilayer Solid Capacitor – JEB

FEATURES

- Endurance: 2,000 hours at 105°C
- Low ESR
- Recommended Applications: System Board, Display Card, Small Charger and intelligent TV
- RoHS Compliance & Lead Free



SPECIFICATIONS

Category Temperature Range	55 ~ +105°C
Rated Working Voltage Range	2 ~ 25 Vdc
Nominal Capacitance Range	6.8~ 680μF
Capacitance Tolerance	±20% (M) ; -35%~+10% (L) ; -10%~+20% (V) ; 0~+20% (A) at 120°C; 120Hz
DC Leakage Current	1 ≤ 0.1CV

Where, I: Leakage current (μA),C: Nominal capacitance (μF},V: Rated voltage M (at 20°C after 2 minutes)

Dissipation Factor (tan δ)	Rated Voltage (Vdc)	2	2.5	4	6.3	7.5	10	12.5	16	20	25	At 20°C,120Hz
	Dissipation Factor (max)	0.06					0.08					

ESR (100kHz, 20°C) Value In characteristics table; Divided into two levels: A/B

Temperature Characteristics
 $Z(+105^{\circ}C)/Z(+20^{\circ}C) \leq 1.25$
 $Z(-55^{\circ}C) / Z(+20^{\circ}C) \leq 1.25$

After applying rated voltage for 2,000 hours at 105°C, the capacitors shall meet the following requirements.

Endurance	Appearance	No significant damage
	Capacitance Change	≤ ±20% of the Initial value
	Dissipation Factor	≤ 150% of the initial specified value
	ESR	≤ 150% of the initial specified value
	Leakage Current	≤ The initial specified value


After subjecting to 90%~95% RH for 500 hours at 60°C(no voltage), the capacitors shall meet the requirements as Endurance.

Humidity Test	Rated Voltage {Vdc)	2~2.5	4	6.3~7.5	8~16	25
	Capacitance Change	+70, -20%	+60, -20%	+50, -20%	+40, -20%	
	D.F. (tan δ)	≤ 200% of the initial specified value				
	Leakage Current	The initial specified value				

After subjecting to 1,000 cycles each consisting of charge with the surge voltage specified at normal temperature for 30 seconds through a protective resistor and discharge for 5 minutes 30 seconds, the capacitors shall meet the following requirements.

Surge Test	Appearance	No significant damage
	Capacitance Change	≤ ±20% of the Initial value
	Dissipation Factor	≤ 150% of the initial specified value
	ESR	≤ 150% of the initial specified value
	Leakage Current	≤ The initial specified value

Drawing (unit: mm):



Case Size	L ± 0.3	W1 ± 0.2	T ± 0.1	W1 ± 0.2	S ± 0.2
7.3x4.3x2.8	7.3	4.3	2.8	2.4	1.3

Please visit our website to get more update data, those data & specification are subject to change without notice.

SMD Multilayer Solid Capacitor – JEB

Characteristics Table:

WV(Vdc)	Cap(μF)	Size (LxWxT mm)	ESR(A)mΩ20°C, 100kHz (max.)	ESR(B)mΩ20°C, 100kHz (max.)	Rated ripple current(A) (mArms)100Khz	Rated ripple current(B) (mArms)100Khz	Leakage current (μA max.)20°C
2	100	7.3*4.3*2.8	12	16	2200	2000	20
	150	7.3*4.3*2.8	6	9	3200	3000	30
	220	7.3*4.3*2.8	6	9	3400	3200	44
	270	7.3*4.3*2.8	6	9	3800	3500	54
	300	7.3*4.3*2.8	6	9	3850	3600	60
	330	7.3*4.3*2.8	4.5	8	4100	3800	66
	390	7.3*4.3*2.8	4.5	8	4250	3900	78
	470	7.3*4.3*2.8	4.5	8	4400	4000	94
	560	7.3*4.3*2.8	4.5	8	4800	4400	112
2.5	100	7.3*4.3*2.8	12	16	2200	2000	25
	150	7.3*4.3*2.8	6	9	3200	3000	38
	180	7.3*4.3*2.8	6	9	3300	3100	45
	220	7.3*4.3*2.8	6	9	3400	3200	55
	270	7.3*4.3*2.8	6	9	3800	3500	68
	330	7.3*4.3*2.8	4.5	8	4100	3800	83
	470	7.3*4.3*2.8	4.5	8	4400	4000	118
	560	7.3*4.3*2.8	4.5	8	4800	4400	140
4	82	7.3*4.3*2.8	12	16	2250	2100	33
	150	7.3*4.3*2.8	12	16	2500	2300	60
	220	7.3*4.3*2.8	12	16	2950	2700	88
	330	7.3*4.3*2.8	12	16	3200	2900	132
6.3	22	7.3*4.3*2.8	35	45	1250	1150	6
	33	7.3*4.3*2.8	35	45	2000	1800	14
	47	7.3*4.3*2.8	25	40	2200	2000	21
	68	7.3*4.3*2.8	12	15	2400	2200	30
	100	7.3*4.3*2.8	12	15	2750	2500	43
	120	7.3*4.3*2.8	10	15	3200	2900	63
	150	7.3*4.3*2.8	9	15	3300	3000	76
	180	7.3*4.3*2.8	9	14	3600	3200	95
	220	7.3*4.3*2.8	9	14	3750	3300	113
	270	7.3*4.3*2.8	7	12	4000	3600	170

SMD Multilayer Solid Capacitor – JEB

Characteristics Table:

WV(Vdc)	Cap(μF)	Size (LxWxT mm)	ESR(A)mΩ20°C, 100kHz (max.)	ESR(B)mΩ20°C, 100kHz (max.)	Rated ripple current(A) (mArms)100Khz	Rated ripple current(B) (mArms)100Khz	Leakage current (μA max.)20°C
10	22	7.3*4.3*2.8	35	45	1700	1600	22
	27	7.3*4.3*2.8	18	30	1800	1700	27
	33	7.3*4.3*2.8	18	30	2000	1800	33
	39	7.3*4.3*2.8	18	30	2050	1850	39
	47	7.3*4.3*2.8	18	30	2200	1950	47
	68	7.3*4.3*2.8	18	30	2300	2050	68
	100	7.3*4.3*2.8	18	30	2750	2500	100
	150	7.3*4.3*2.8	16	25	3100	2800	150
16	6.8	7.3*4.3*2.8	56	70	1100	1000	11
	15	7.3*4.3*2.8	45	60	1200	1100	16
	15	7.3*4.3*2.8	25	60	1300	1200	24
	22	7.3*4.3*2.8	18	40	1500	1400	35
	33	7.3*4.3*2.8	18	30	1750	1600	53
	47	7.3*4.3*2.8	18	30	1850	1700	75
	68	7.3*4.3*2.8	18	30	2000	1850	109
	100	7.3*4.3*2.8	18	30	2350	2100	160
	150	7.3*4.3*2.8	16	28	2550	2300	240
25	6.8	7.3*4.3*2.8	56	70	1200	1100	17
	10	7.3*4.3*2.8	45	60	1400	1200	25
	15	7.3*4.3*2.8	40	55	1550	1400	38
	22	7.3*4.3*2.8	28	40	1600	1450	55
	33	7.3*4.3*2.8	28	40	1650	1500	83
	47	7.3*4.3*2.8	28	40	1800	1600	118
	68	7.3*4.3*2.8	25	36	1900	1700	170
	100	7.3*4.3*2.8	21	30	2100	1900	250

Please visit our website to get more update data, those data & specification are subject to change without notice.